

## PRODUCT DATA SHEET

**SPEC#:** 246A  
**PART#:** 20029850  
**PRODUCT:** 1-Ply 440# 1/4 x 1/8 Grade 1

SPECIFICATIONS			
<b>Plies</b>	1	<b>Temp. Range</b>	-25°F to 225°F
<b>Working Tension</b>	440	<b>MSHA Approved/ Fire Resistant</b>	N/A
<b>Carcass</b>	Straight Warp Polyester/Nylon	<b>Oil Resistant</b>	No
<b>Color</b>	Black	<b>Durometer</b>	60 +/- 5
<b>Compound</b>	SBR Blend	<b>Mechanical Fasteners</b>  <i>Clipper</i> <sup>®</sup> Not Recommended <i>Alligator</i> <sup>®</sup> Not Recommended <i>Staple</i> Not Recommended <i>Solid Plate</i> #190 <i>Flexco</i> <sup>®</sup> Bolt Hinge #550 <i>Flexco</i> <sup>®</sup> Rivet #R6	
<b>Top Surface</b>	Smooth Cover		
<b>Bottom Surface</b>	Smooth		
<b>Profile</b>	N/A		
<b>Overall Gauge</b>	9/16"		
<b>Weight PIW</b>	0.295		
<b>Elongation @ 100% Rated Working Tension</b>	1-2%		
<b>Minimum Pulley Head</b>	20"		
<b>Minimum Pulley Tail</b>	20"		
<b>Minimum Pulley Elevator</b>	N/A		

Specifications are subject to change without notice