

## PRODUCT DATA SHEET

**SPEC#:** 2  
**PART#:** 20027301  
**PRODUCT:** 2-Ply 150# 1/32 x 1/32 Grade 2

| SPECIFICATIONS                                     |                 |   |                |
|--|-----------------|---|----------------|
| <b>Plies</b>                                       | 2               | <b>Temp. Range</b>  | -25°F to 225°F |
| <b>Working Tension</b>                             | 150             | <b>MSHA Approved/<br/>Fire Resistant</b>  | N/A            |
| <b>Carcass</b>                                     | Polyester/Nylon | <b>Oil Resistant</b>  | No             |
| <b>Color</b>                                       | Black           | <b>Durometer</b>  | 60 +/- 5       |
| <b>Compound</b>                                    | SBR             | <b>Mechanical Fasteners</b><br><br><i>Clipper</i> <sup>®</sup> #3<br><i>Alligator</i> <sup>®</sup> #25<br><i>Staple</i> #187<br><i>Solid Plate</i> Not Recommended<br><i>Flexco</i> <sup>®</sup> <i>Bolt Hinge</i> Not Recommended<br><i>Flexco</i> <sup>®</sup> <i>Rivet</i> Not Recommended |                |
| <b>Top Surface</b>                                 | Smooth Cover    |   |                |
| <b>Bottom Surface</b>                              | Smooth          |   |                |
| <b>Profile</b>                                     | N/A             |   |                |
| <b>Overall Gauge</b>                               | 3/16"           |   |                |
| <b>Weight PIW</b>                                  | 0.085           |   |                |
| <b>Elongation @ 100%<br/>Rated Working Tension</b> | 1-2%            |   |                |
| <b>Minimum Pulley Head</b>                         | 4"              |   |                |
| <b>Minimum Pulley Tail</b>                         | 4"              |   |                |
| <b>Minimum Pulley Elevator</b>                     | N/A             |   |                |

*Specifications are subject to change without notice*