

## PRODUCT DATA SHEET

**SPEC#:** 11  
**PART#:** 20023005  
**PRODUCT:** 3-Ply 330# 3/16 x 1/16 Grade 2

SPECIFICATIONS			
<b>Plies</b>	3	<b>Temp. Range</b>	-25°F to 225°F
<b>Working Tension</b>	330	<b>MSHA Approved/ Fire Resistant</b>	N/A
<b>Carcass</b>	Polyester/Nylon	<b>Oil Resistant</b>	No
<b>Color</b>	Black	<b>Durometer</b>	60 +/- 5
<b>Compound</b>	SBR	<b>Mechanical Fasteners</b>  <i>Clipper</i> <sup>®</sup> Not Recommended <i>Alligator</i> <sup>®</sup> Not Recommended <i>Staple</i> Not Recommended <i>Solid Plate</i> #190 <i>Flexco</i> <sup>®</sup> <i>Bolt Hinge</i> #550 <i>Flexco</i> <sup>®</sup> <i>Rivet</i> #R5-1/2	
<b>Top Surface</b>	Smooth Cover		
<b>Bottom Surface</b>	Smooth		
<b>Profile</b>	N/A		
<b>Overall Gauge</b>	13/32"		
<b>Weight PIW</b>	0.205		
<b>Elongation @ 100% Rated Working Tension</b>	1-2%		
<b>Minimum Pulley Head</b>	16"		
<b>Minimum Pulley Tail</b>	16"		
<b>Minimum Pulley Elevator</b>	N/A		

*Specifications are subject to change without notice*