

## PRODUCT DATA SHEET

**SPEC#:** 12  
**PART#:** 20026039  
**PRODUCT:** 3-Ply 330# 1/4 x 1/16 Grade 2

SPECIFICATIONS			
	<b>Plies</b>	3	
	<b>Working Tension</b>	330	<b>Temp. Range</b>
	<b>Carcass</b>	Polyester/Nylon	-25°F to 225°F
	<b>Color</b>	Black	<b>MSHA Approved/ Fire Resistant</b>
	<b>Compound</b>	SBR	N/A
	<b>Top Surface</b>	Smooth Cover	<b>Oil Resistant</b>
	<b>Bottom Surface</b>	Smooth	No
	<b>Profile</b>	N/A	<b>Durometer</b>
	<b>Overall Gauge</b>	15/32"	60 +/- 5
	<b>Weight PIW</b>	0.215	
	<b>Elongation @ 100% Rated Working Tension</b>	1-2%	<b>Mechanical Fasteners</b>
	<b>Minimum Pulley Head</b>	16"	<b><i>Clipper</i></b> <sup>®</sup>
	<b>Minimum Pulley Tail</b>	16"	Not Recommended
	<b>Minimum Pulley Elevator</b>	N/A	<b><i>Alligator</i></b> <sup>®</sup>
			Not Recommended
			<b><i>Staple</i></b>
			Not Recommended
			<b><i>Solid Plate</i></b>
			#190
			<b><i>Flexco</i></b> <sup>®</sup> <b><i>Bolt Hinge</i></b>
			#550
			<b><i>Flexco</i></b> <sup>®</sup> <b><i>Rivet</i></b>
			#R5-1/2

*Specifications are subject to change without notice*