

PRODUCT DATA SHEET

SPEC#: 26B
PART#: 20029734
PRODUCT: 3-Ply 330# 3/16 x Bare Back Moderate Oil Resistance

| SPECIFICATIONS | | | |
|--|-----------------|---|--------------|
| Plies | 3 | Temp. Range | 0°F to 250°F |
| Working Tension | 330 | MSHA Approved/ Fire Resistant | N/A |
| Carcass | Polyester/Nylon | Oil Resistant | Yes |
| Color | Black | Durometer | 60 +/- 5 |
| Compound | Nitrile Blend | Mechanical Fasteners <i>Clipper</i> [®] Not Recommended <i>Alligator</i> [®] Not Recommended <i>Staple</i> Not Recommended <i>Solid Plate</i> #190 <i>Flexco</i> [®] <i>Bolt Hinge</i> #375 <i>Flexco</i> [®] <i>Rivet</i> #R5 | |
| Top Surface | Smooth Cover | | |
| Bottom Surface | Bare | | |
| Profile | N/A | | |
| Overall Gauge | 11/32" | | |
| Weight PIW | 0.180 | | |
| Elongation @ 100% Rated Working Tension | 1-2% | | |
| Minimum Pulley Head | 16" | | |
| Minimum Pulley Tail | 16" | | |
| Minimum Pulley Elevator | N/A | | |

Specifications are subject to change without notice