

## PRODUCT DATA SHEET

**SPEC#:** 42  
**PART#:** 20021030  
**PRODUCT:** 2-Ply 220# 3/16 x 1/16 350° Super Oil Resistant Hot Asphalt

SPECIFICATIONS			
<b>Plies</b>	2	<b>Temp. Range</b>	0°F to 350°F
<b>Working Tension</b>	220	<b>MSHA Approved/ Fire Resistant</b>	N/A
<b>Carcass</b>	Polyester/Nylon	<b>Oil Resistant</b>	Yes
<b>Color</b>	Black	<b>Durometer</b>	60 +/- 5
<b>Compound</b>	Nitrile	<b>Mechanical Fasteners</b>	
<b>Top Surface</b>	Smooth Cover	<b>Clipper®</b>	Not Recommended
<b>Bottom Surface</b>	Smooth	<b>Alligator®</b>	Not Recommended
<b>Profile</b>	N/A	<b>Staple</b>	Not Recommended
<b>Overall Gauge</b>	3/8"	<b>Solid Plate</b>	#190
<b>Weight PIW</b>	0.195	<b>Flexco® Bolt Hinge</b>	#550
<b>Elongation @ 100% Rated Working Tension</b>	1-2%	<b>Flexco® Rivet</b>	#R5
<b>Minimum Pulley Head</b>	12"		
<b>Minimum Pulley Tail</b>	12"		
<b>Minimum Pulley Elevator</b>	N/A		

*Specifications are subject to change without notice*