

## PRODUCT DATA SHEET

**SPEC#:** 177  
**PART#:** 20026766  
**PRODUCT:** 3-Ply 330# 1/4 x 1/16 400° Maxi-Heat

SPECIFICATIONS				
	<b>Plies</b>	3		
	<b>Working Tension</b>	330	<b>Temp. Range</b> 400°F for 2"+ lumps, 300°F for fines & dense/baking loads	
	<b>Carcass</b>	Polyester/Nylon		
	<b>Color</b>	Black	<b>MSHA Approved/ Fire Resistant</b> N/A	
	<b>Compound</b>	EPDM		
	<b>Top Surface</b>	Smooth Cover	<b>Oil Resistant</b> No	
	<b>Bottom Surface</b>	Smooth		
	<b>Profile</b>	N/A	<b>Durometer</b> 60 +/- 5	
	<b>Overall Gauge</b>	1/2"		
	<b>Weight PIW</b>	0.232	<b>Mechanical Fasteners</b>	
	<b>Elongation @ 100% Rated Working Tension</b>	1-2%		
	<b>Minimum Pulley Head</b>	18"		
	<b>Minimum Pulley Tail</b>	18"		
	<b>Minimum Pulley Elevator</b>	N/A		
				<b>Clipper®</b> Not Recommended
				<b>Alligator®</b> Not Recommended
				<b>Staple</b> Not Recommended
			<b>Solid Plate</b> #190	
			<b>Flexco® Bolt Hinge</b> #550	
			<b>Flexco® Rivet</b> #R5-1/2	

*Specifications are subject to change without notice*