

## PRODUCT DATA SHEET

**SPEC#:** 247  
**PART#:** 20029607  
**PRODUCT:** 3-Ply 330# 1/8 x Bare Back Durocleat Moderate Oil Resistance

SPECIFICATIONS			
<b>Plies</b>	3	<b>Temp. Range</b>	0°F to 250°F
<b>Working Tension</b>	330	<b>MSHA Approved/ Fire Resistant</b>	N/A
<b>Carcass</b>	Polyester/Nylon	<b>Oil Resistant</b>	Yes
<b>Color</b>	Black	<b>Durometer</b>	60 +/- 5
<b>Compound</b>	Nitrile Blend	<b>Mechanical Fasteners</b>  <i>Clipper</i> <sup>®</sup> Not Recommended <i>Alligator</i> <sup>®</sup> Not Recommended <i>Staple</i> Not Recommended <i>Solid Plate</i> #190 <i>Flexco</i> <sup>®</sup> <i>Bolt Hinge</i> #550 <i>Flexco</i> <sup>®</sup> <i>Rivet</i> #R5	
<b>Top Surface</b>	Molded Chevron		
<b>Bottom Surface</b>	Bare		
<b>Profile</b>	1/4" x 3/8"		
<b>Overall Gauge</b>	.337"		
<b>Weight PIW</b>	0.225		
<b>Elongation @ 100% Rated Working Tension</b>	1-2%		
<b>Minimum Pulley Head</b>	12"		
<b>Minimum Pulley Tail</b>	12"		
<b>Minimum Pulley Elevator</b>	N/A		

*Specifications are subject to change without notice*