

PRODUCT DATA SHEET

SPEC#: 25A
PART#: 20021630
PRODUCT: 3-Ply 330# 1/16 x 1/16 Static Conductive Oil Resistant Fire Retardant Grain

| SPECIFICATIONS | | | |
|--|-----------------|--|-----------------|
| Plies | 3 | Temp. Range | 0°F to 250°F |
| Working Tension | 330 | MSHA Approved/ Fire Resistant | Yes |
| Carcass | Polyester/Nylon | Oil Resistant | Yes |
| Color | Black | Durometer | 60 +/- 5 |
| Compound | Nitrile | Mechanical Fasteners | |
| Top Surface | Smooth Cover | Clipper® | Not Recommended |
| Bottom Surface | Smooth | Alligator® | Not Recommended |
| Profile | N/A | Staple | Not Recommended |
| Overall Gauge | 17/64" | Solid Plate | #140 |
| Weight PIW | 0.130 | Flexco® Bolt Hinge | #550 |
| Elongation @ 100% Rated Working Tension | 1-2% | Flexco® Rivet | #R5 |
| Minimum Pulley Head | 16" | | |
| Minimum Pulley Tail | 16" | | |
| Minimum Pulley Elevator | 18" | | |

Specifications are subject to change without notice