

## PRODUCT DATA SHEET

**SPEC#:** 2033  
**PART#:** 20102033  
**PRODUCT:** FEMW-2.5 ITO 50  
 Volta FEMW-2.5 ITO 50 Homogeneous Cream TPE Impression x Embossed

SPECIFICATIONS			
<b>Plies</b>	N/A	<b>Temp. Range</b>	-20°F to 140°F
<b>Working Tension</b>	N/A	<b>Accepted</b>	FDA, USDA, EU, 3A Dairy
<b>Carcass</b>	Homogeneous	<b>Endless Splice</b>	Butt Splice
<b>Color</b>	Cream		
<b>Compound</b>	TPE	<b>Fasteners</b>	
<b>Top Surface</b>	Impression	<b>Clipper®</b>	UX1SP
<b>Bottom Surface</b>	Embossed	<b>Alligator®</b>	#7
<b>Overall Gauge</b>	2.5 mm	<b>Staple</b>	RS62
<b>Weight PIW</b>	0.044	<b>Solid Plate</b>	Not Recommended
<b>Elongation @ 100%</b>	NA	<b>Flexco® Bolt Hinge</b>	Not Recommended
<b>Rated Working Tension</b>		<b>Flexco® Rivet</b>	Not Recommended
<b>Minimum Pulley</b>	1.375"	<b>Plastic Spiral</b>	Not Recommended
		<b>Plastic Rivet</b>	APF150 W

Specifications are subject to change without notice