

## PRODUCT DATA SHEET

**SPEC#:** 3852  
**PART#:** 20103852  
**PRODUCT:** PU 2M 65 BLU CxB Non Fray  
 2-Ply 65# Polyester Blue Urethane Cover x Bare (Non Fray)

SPECIFICATIONS			
<b>Plies</b>	2	<b>Temp. Range</b>	0°F to 180°F
<b>Working Tension</b>	65	<b>Accepted</b>	FDA, EU
<b>Carcass</b>	Polyester	<b>Endless Splice</b>	Finger, Skive
<b>Color</b>	Blue	<b>Fasteners</b> <i>Clipper</i> <sup>®</sup> UCM36SP <i>Alligator</i> <sup>®</sup> #1 <i>Staple</i> RS62 <i>Solid Plate</i> Not Recommended <i>Flexco</i> <sup>®</sup> <i>Bolt Hinge</i> Not Recommended <i>Flexco</i> <sup>®</sup> <i>Rivet</i> Not Recommended <i>Plastic Spiral</i> ASL90 <i>Plastic Rivet</i> APF100 W	
<b>Compound</b>	Urethane		
<b>Top Surface</b>	Matte Cover		
<b>Bottom Surface</b>	Bare		
<b>Overall Gauge</b>	0.062"		
<b>Weight PIW</b>	0.022		
<b>Elongation @ 100% Rated Working Tension</b>	1-2%		
<b>Minimum Pulley</b>	.5"		

*Specifications are subject to change without notice*