

## PRODUCT DATA SHEET

**SPEC#:** 4117  
**PART#:** 20104117  
**PRODUCT:** 3-Ply 105 HS&W CottonxFS  
 3-Ply 105# Cotton/Polyester White HS&W Cotton x Friction

SPECIFICATIONS			
<b>Plies</b>	3	<b>Temp. Range</b>	0°F to 250°F
<b>Working Tension</b>	105	<b>Accepted</b>	N/A
<b>Carcass</b>	Cotton/Polyester	<b>Endless Splice</b>	Bias Step
<b>Color</b>	White		
<b>Compound</b>	SBR	<b>Fasteners</b>	
<b>Top Surface</b>	Bare	<b>Clipper®</b>	UX1
<b>Bottom Surface</b>	Friction	<b>Alligator®</b>	#15
<b>Overall Gauge</b>	0.125"	<b>Staple</b>	RS125
<b>Weight PIW</b>	0.066	<b>Solid Plate</b>	Not Recommended
<b>Elongation @ 100% Rated Working Tension</b>	1-2%	<b>Flexco® Bolt Hinge</b>	Not Recommended
<b>Minimum Pulley</b>	2.5"	<b>Flexco® Rivet</b>	Not Recommended
		<b>Plastic Spiral</b>	ASL90
		<b>Plastic Rivet</b>	APF150 W

*Specifications are subject to change without notice*