

## PRODUCT DATA SHEET

**SPEC#:** 4129  
**PART#:** 20104129  
**PRODUCT:** 4-Ply 90 TAN SBR NYLON TOPxFS  
 4-Ply 90# Sliptop Polyester Tan Nitrile Bare Nylon x Friction

SPECIFICATIONS			
<b>Plies</b>	4	<b>Temp. Range</b>	20°F to 212°F
<b>Working Tension</b>	90	<b>Accepted</b>	N/A
<b>Carcass</b>	Polyester	<b>Endless Splice</b>	Bias Step
<b>Color</b>	Tan		
<b>Compound</b>	Nitrile	<b>Fasteners</b>	
<b>Top Surface</b>	Bare	<b>Clipper®</b>	UX1
<b>Bottom Surface</b>	Friction	<b>Alligator®</b>	7
<b>Overall Gauge</b>	0.125"	<b>Staple</b>	RS125
<b>Weight PIW</b>	0.070	<b>Solid Plate</b>	Not Recommended
<b>Elongation @ 100% Rated Working Tension</b>	1-2%	<b>Flexco® Bolt Hinge</b>	Not Recommended
<b>Minimum Pulley</b>	2"	<b>Flexco® Rivet</b>	Not Recommended
		<b>Plastic Spiral</b>	ASL90
		<b>Plastic Rivet</b>	APF150 W

*Specifications are subject to change without notice*