

## PRODUCT DATA SHEET

**SPEC#:** 4151  
**PART#:** 20104151  
**PRODUCT:** PU 120 RED CxBR  
 Interwoven 120# Polyester Red Urethane Cover x Brushed

| SPECIFICATIONS                                     |                |                           |                 |
|--|----------------|---------------------------|-----------------|
| <b>Plies</b>                                       | IWP            | <b>Temp. Range</b>        | 0°F to 180°F    |
| <b>Working Tension</b>                             | 120            | <b>Accepted</b>           | N/A             |
| <b>Carcass</b>                                     | Interwoven     | <b>Endless Splice</b>     | Finger, Skive   |
| <b>Color</b>                                       | Red            |                           |                 |
| <b>Compound</b>                                    | Urethane       | <b>Fasteners</b>          |                 |
| <b>Top Surface</b>                                 | Urethane Cover | <b>Clipper®</b>           | U2              |
| <b>Bottom Surface</b>                              | Brushed        | <b>Alligator®</b>         | #20             |
| <b>Overall Gauge</b>                               | 0.1875"        | <b>Staple</b>             | RS187           |
| <b>Weight PIW</b>                                  | 0.094          | <b>Solid Plate</b>        | Not Recommended |
| <b>Elongation @ 100%<br/>Rated Working Tension</b> | 1-2%           | <b>Flexco® Bolt Hinge</b> | Not Recommended |
| <b>Minimum Pulley</b>                              | 4"             | <b>Flexco® Rivet</b>      | Not Recommended |
|  |                | <b>Plastic Spiral</b>     | ASL90           |
|  |                | <b>Plastic Rivet</b>      | APF150 W Recess |

*Specifications are subject to change without notice*