

## PRODUCT DATA SHEET

**SPEC#:** 4311  
**PART#:** 20104311  
**PRODUCT:** 3-Ply 150 TAN GUM V-TOPxFS  
 3-Ply 150# Polyester/Nylon Tan Pure Gum V-Top x Friction

SPECIFICATIONS			
<b>Plies</b>	3	<b>Temp. Range</b>	-30°F to 180°F
<b>Working Tension</b>	150	<b>Accepted</b>	N/A
<b>Carcass</b>	Polyester/Nylon	<b>Endless Splice</b>	Bias Step
<b>Color</b>	Tan	<b>Fasteners</b> <i>Clipper</i> <sup>®</sup> 2 <i>Alligator</i> <sup>®</sup> #25 <i>Staple</i> RS125 <i>Solid Plate</i> Not Recommended <i>Flexco</i> <sup>®</sup> <i>Bolt Hinge</i> Not Recommended <i>Flexco</i> <sup>®</sup> <i>Rivet</i> Not Recommended <i>Plastic Spiral</i> ASL90 <i>Plastic Rivet</i> APF150 W	
<b>Compound</b>	Pure Gum		
<b>Top Surface</b>	Impression		
<b>Bottom Surface</b>	Friction		
<b>Overall Gauge</b>	0.297"		
<b>Weight PIW</b>	0.080		
<b>Elongation @ 100% Rated Working Tension</b>	1-2%		
<b>Minimum Pulley</b>	4"		

*Specifications are subject to change without notice*