

## PRODUCT DATA SHEET

**SPEC#:** 4312  
**PART#:** 20104312  
**PRODUCT:** 3-Ply 150 BLK SBR V-TOPxFS  
 3-Ply 105# Cotton/Polyester Black SBR V-Top x Friction

| SPECIFICATIONS                                     |                  |                           |                 |
|--|------------------|---------------------------|-----------------|
| <b>Plies</b>                                       | 3                | <b>Temp. Range</b>        | 0°F to 250°F    |
| <b>Working Tension</b>                             | 105              | <b>Accepted</b>           | N/A             |
| <b>Carcass</b>                                     | Cotton/Polyester | <b>Endless Splice</b>     | Bias Step       |
| <b>Color</b>                                       | Black            |                           |                 |
| <b>Compound</b>                                    | SBR              | <b>Fasteners</b>          |                 |
| <b>Top Surface</b>                                 | Impression       | <b>Clipper®</b>           | U2              |
| <b>Bottom Surface</b>                              | Friction         | <b>Alligator®</b>         | #15             |
| <b>Overall Gauge</b>                               | 0.313"           | <b>Staple</b>             | RS125           |
| <b>Weight PIW</b>                                  | 0.120            | <b>Solid Plate</b>        | Not Recommended |
| <b>Elongation @ 100%<br/>Rated Working Tension</b> | 1-2%             | <b>Flexco® Bolt Hinge</b> | Not Recommended |
| <b>Minimum Pulley</b>                              | 2.5"             | <b>Flexco® Rivet</b>      | Not Recommended |
|  |                  | <b>Plastic Spiral</b>     | ASL90           |
|  |                  | <b>Plastic Rivet</b>      | APF150 B        |

*Specifications are subject to change without notice*