

## PRODUCT DATA SHEET

**SPEC#:** 284  
**PART#:** 20026819  
**PRODUCT:** 4-Ply 440# 1/4 x 3/32 400° Maxi-Heat

SPECIFICATIONS			
	<b>Plies</b>	4	
	<b>Working Tension</b>	440	<b>Temp. Range</b> 400°F for 2"+ lumps, 300°F for fines & dense/baking loads
	<b>Carcass</b>	Polyester/Nylon	
	<b>Color</b>	Black	<b>MSHA Approved/ Fire Resistant</b> N/A
	<b>Compound</b>	EPDM	<b>Oil Resistant</b> No
	<b>Top Surface</b>	Smooth Cover	<b>Durometer</b> 65
	<b>Bottom Surface</b>	Smooth	
	<b>Profile</b>	N/A	<b>Mechanical Fasteners</b>
	<b>Overall Gauge</b>	19/32"	<b>Clipper®</b> Not Recommended
	<b>Weight PIW</b>	0.295	<b>Alligator®</b> Not Recommended
	<b>Elongation @ 100% Rated Working Tension</b>	1.5-2%	<b>Staple</b> Not Recommended
	<b>Minimum Pulley Head</b>	20"	<b>Solid Plate</b> #190
	<b>Minimum Pulley Tail</b>	20"	<b>Flexco® Bolt Hinge</b> #550
	<b>Minimum Pulley Elevator</b>	24"	<b>Flexco® Rivet</b> #R6

*Specifications are subject to change without notice*