

PRODUCT DATA SHEET

SPEC#: 403
PART#: 20027014
PRODUCT: 4-Ply 800# 1/4 x Bare Moderate Oil Resistance

SPECIFICATIONS			
Plies	4	Temp. Range	0°F to 250°F
Working Tension	800	MSHA Approved/ Fire Resistant	N/A
Carcass	Polyester/Nylon	Oil Resistant	Yes
Color	Black	Durometer	60
Compound	NBR Blend	Mechanical Fasteners <i>Clipper</i> [®] Not Recommended <i>Alligator</i> [®] Not Recommended <i>Staple</i> Not Recommended <i>Solid Plate</i> #1-1/2 <i>Flexco</i> [®] <i>Bolt Hinge</i> #550 <i>Flexco</i> [®] <i>Rivet</i> #R5-1/2	
Top Surface	Smooth		
Bottom Surface	Bare		
Profile	N/A		
Overall Gauge	15/32"		
Weight PIW	0.285		
Elongation @ 100% Rated Working Tension	1.5–2%		
Minimum Pulley Head	24"		
Minimum Pulley Tail	20"		
Minimum Pulley Elevator	N/A		

*Specifications are subject to change without notice
Contact Portland at 503.467.4671 for pricing and delivery*