

## PRODUCT DATA SHEET

**SPEC#:** 401  
**PART#:** 20027012  
**PRODUCT:** 4-Ply 800# 1/2 x 1/8 Grade 1

| SPECIFICATIONS                                     |                 |  |                |
|--|-----------------|--|----------------|
| <b>Plies</b>                                       | 4               | <b>Temp. Range</b>   | -25°F to 225°F |
| <b>Working Tension</b>                             | 800             | <b>MSHA Approved/<br/>Fire Resistant</b>   | N/A            |
| <b>Carcass</b>                                     | Polyester/Nylon | <b>Oil Resistant</b>   | No             |
| <b>Color</b>                                       | Black           | <b>Durometer</b>   | 60             |
| <b>Compound</b>                                    | NR/SBR          | <b>Mechanical Fasteners</b><br><br><i>Clipper</i> <sup>®</sup> Not Recommended<br><i>Alligator</i> <sup>®</sup> Not Recommended<br><i>Staple</i> Not Recommended<br><i>Solid Plate</i> #2-1/4<br><i>Flexco</i> <sup>®</sup> <i>Bolt Hinge</i> Not Recommended<br><i>Flexco</i> <sup>®</sup> <i>Rivet</i> #R9 |                |
| <b>Top Surface</b>                                 | Smooth          |  |                |
| <b>Bottom Surface</b>                              | Smooth          |  |                |
| <b>Profile</b>                                     | N/A             |  |                |
| <b>Overall Gauge</b>                               | 7/8"            |  |                |
| <b>Weight PIW</b>                                  | 0.475           |  |                |
| <b>Elongation @ 100%<br/>Rated Working Tension</b> | 1.5–2%          |  |                |
| <b>Minimum Pulley Head</b>                         | 24"             |  |                |
| <b>Minimum Pulley Tail</b>                         | 20"             |  |                |
| <b>Minimum Pulley Elevator</b>                     | 36"             |  |                |

*Specifications are subject to change without notice  
Contact Portland at 503.467.4671 for pricing and delivery*