

## PRODUCT DATA SHEET

**SPEC#:** 401  
**PART#:** 20027012  
**PRODUCT:** 4-Ply 800# 1/2 x 1/8 Grade 1

SPECIFICATIONS			
	<b>Plies</b>	4	
	<b>Working Tension</b>	800	<b>Temp. Range</b>
	<b>Carcass</b>	Polyester/Nylon	-25°F to 225°F
	<b>Color</b>	Black	<b>MSHA Approved/ Fire Resistant</b>
	<b>Compound</b>	NR/SBR	N/A
	<b>Top Surface</b>	Smooth	<b>Oil Resistant</b>
	<b>Bottom Surface</b>	Smooth	No
	<b>Profile</b>	N/A	<b>Durometer</b>
	<b>Overall Gauge</b>	7/8"	60
	<b>Weight PIW</b>	0.475	<b>Mechanical Fasteners</b>
	<b>Elongation @ 100% Rated Working Tension</b>	1.5–2%	<b>Clipper®</b>
	<b>Minimum Pulley Head</b>	24"	Not Recommended
	<b>Minimum Pulley Tail</b>	20"	<b>Alligator®</b>
	<b>Minimum Pulley Elevator</b>	36"	Not Recommended
			<b>Staple</b>
			Not Recommended
			<b>Solid Plate</b>
			#2-1/4
			<b>Flexco® Bolt Hinge</b>
			Not Recommended
			<b>Flexco® Rivet</b>
			#R9

*Specifications are subject to change without notice  
 Contact Portland at 503.467.4671 for pricing and delivery*