

## PRODUCT DATA SHEET

**SPEC#:** 300  
**PART#:** 20021637  
**PRODUCT:** 3-Ply 600# 1/4 x Bare Moderate Oil Resistance

SPECIFICATIONS			
<b>Plies</b>	3	<b>Temp. Range</b>	0°F to 250°F
<b>Working Tension</b>	600	<b>MSHA Approved/ Fire Resistant</b>	N/A
<b>Carcass</b>	Polyester/Nylon	<b>Oil Resistant</b>	Yes
<b>Color</b>	Black	<b>Durometer</b>	60
<b>Compound</b>	NBR Blend	<b>Mechanical Fasteners</b>	
<b>Top Surface</b>	Smooth	<b>Clipper®</b>	Not Recommended
<b>Bottom Surface</b>	Bare	<b>Alligator®</b>	Not Recommended
<b>Profile</b>	N/A	<b>Staple</b>	Not Recommended
<b>Overall Gauge</b>	7/16"	<b>Solid Plate</b>	#2
<b>Weight PIW</b>	0.245	<b>Flexco® Bolt Hinge</b>	#550
<b>Elongation @ 100% Rated Working Tension</b>	1.5–2%	<b>Flexco® Rivet</b>	#R5-1/2
<b>Minimum Pulley Head</b>	20"		
<b>Minimum Pulley Tail</b>	18"		
<b>Minimum Pulley Elevator</b>	N/A		

*Specifications are subject to change without notice  
 Contact Portland at 503.467.4671 for pricing and delivery*