

## PRODUCT DATA SHEET

**SPEC#:** 301  
**PART#:** 20029017  
**PRODUCT:** 3-Ply 225# 1/32 x 1/32 Grade 2

SPECIFICATIONS			
<b>Plies</b>	3	<b>Temp. Range</b>	-25°F to 225°F
<b>Working Tension</b>	225	<b>MSHA Approved/ Fire Resistant</b>	N/A
<b>Carcass</b>	Polyester/Nylon	<b>Oil Resistant</b>	No
<b>Color</b>	Black	<b>Durometer</b>	60
<b>Compound</b>	SBR	<b>Mechanical Fasteners</b>  <i>Clipper</i> <sup>®</sup> Not Recommended <i>Alligator</i> <sup>®</sup> Not Recommended <i>Staple</i> RS187 <i>Solid Plate</i> #140 <i>Flexco</i> <sup>®</sup> <i>Bolt Hinge</i> #375 <i>Flexco</i> <sup>®</sup> <i>Rivet</i> #R2	
<b>Top Surface</b>	Smooth		
<b>Bottom Surface</b>	Smooth		
<b>Profile</b>	N/A		
<b>Overall Gauge</b>	1/4"		
<b>Weight PIW</b>	0.120		
<b>Elongation @ 100% Rated Working Tension</b>	1.5–2%		
<b>Minimum Pulley Head</b>	10"		
<b>Minimum Pulley Tail</b>	8"		
<b>Minimum Pulley Elevator</b>	12"		

*Specifications are subject to change without notice  
 Contact Portland at 503.467.4671 for pricing and delivery*